

## DC BLOWER FAN

AG5836B 58\*36mm

Motor:DC Blower Bearing:Ball

Shell frame: PBT UL94V\_0 Fan blade: PBT UL94V\_0


Insulation:Class B

Wire: AWG#26UL1007 (optional)


PIN1:BLACK WIRE---(-) PIN2:RED WIRE---(+)



## DIMENSIONS DRAWING(unit:mm)



## P@Q CURVE(AT RATEDVOLTAGE)



Mode I	Bearing Mode①	Rated Volta ge	Operating voltage range	Rated curre nt	Rated input power	Speed	Maximum air Flow		Maximum Air pressure		Noise
PART. NO.	B=Ball S=Sleeve .H=Hydraulic	VDC	VDC	Amp	Watt	R. P. M	m³/min	CFM	mmH20	InH20	dB-A
AG5836B12H		12	7 <sup>~</sup> 13. 5	1. 6	19. 2	24000	0. 229	8. 12	311. 64	12. 22	55
AG5836B24H		24	14 <sup>~</sup> 27. 5	0.8	19. 2	24000	0. 229	8. 12	311. 64	12. 22	55


①Bearing Mode:Ball/ Sleeve/Hydraulic/Ball(UL)/Sleeve(UL)Hydraulic(UL)

②X=Function: FG RD RDL LD PWM TP VC RC CS RP SS AS CL IPX5

3A=Plug

(4)C=Customized by customers: Air volume, Air duct, Movement, Service life, Temperature, Noise, Material, Mold. etc.

## 导引: 编码规则Code Rule



\*PROPRIETARY AND CONFIDENTIAL , THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF <ALL NEW SEMI>.

ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF <ALL NEW SEMI> IS PROHIBITED.

https://allnewsemi.com https://allnewsemi.shop