

# Hex Inverter

## MM74HC04

### General Description

The MM74HC04 inverters utilize advanced silicon-gate CMOS technology to achieve operating speeds similar to LS-TTL gates with the low power consumption of standard CMOS integrated circuits.

The MM74HC04 is a triple buffered inverter. It has high noise immunity and the ability to drive 10 LS-TTL loads. The 74HC logic family is functionally as well as pin-out compatible with the standard 74LS logic family. All inputs are protected from damage due to static discharge by internal diode clamps to  $V_{CC}$  and ground.

### Features

- Typical Propagation Delay: 8 ns
- Fan Out of 10 LS-TTL Loads
- Quiescent Power Consumption: 10  $\mu$ W Maximum at Room Temperature
- Low Input Current: 1  $\mu$ A Maximum
- These Devices are Pb-Free, Halide Free and are RoHS Compliant

### Connection Diagram





Figure 1. Pin Assignments for SOIC and TSSOP


### Logic Diagram




Figure 2. 1 of 6 Inverters



SOIC-14 NB  
CASE 751A-03





SOIC-14  
CASE 751EF



TSSOP-14 WB  
CASE 948G

### MARKING DIAGRAM



HC04A = Specific Device Code  
A = Assembly Location  
WL, L = Wafer Lot  
Y = Year  
WW, W = Work Week

### ORDERING INFORMATION

See detailed ordering and shipping information on page 4 of this data sheet.

# MM74HC04

## ABSOLUTE MAXIMUM RATINGS (Note 1)

| Symbol           | Parameter                               |                   | Rating                   |
|------------------|-----------------------------------------|-------------------|--------------------------|
| $V_{CC}$         | Supply Voltage                          |                   | –0.5 to +7.0 V           |
| $V_{IN}$         | DC Input Voltage                        |                   | –0.5 to $V_{CC} + 0.5$ V |
| $V_{OUT}$        | DC Output Voltage                       |                   | –0.5 to $V_{CC} + 0.5$ V |
| $I_{IK}, I_{OK}$ | Clamp Diode Current                     |                   | ±20 mA                   |
| $I_{OUT}$        | DC Output Current, per Pin              |                   | ±25 mA                   |
| $I_{CC}$         | DC $V_{CC}$ or GND Current, per Pin     |                   | ±50 mA                   |
| $T_{STG}$        | Storage Temperature Range               |                   | –65°C to +150°C          |
| $P_D$            | Power Dissipation                       | Note 2            | 600 mW                   |
|                  |                                         | S.O. Package Only | 500 mW                   |
| $T_L$            | Lead Temperature (Soldering 10 Seconds) |                   | 260°C                    |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Unless otherwise specified all voltages are referenced to ground.

2. Power Dissipation temperature derating – plastic “N” package: –12 mW/°C from 65°C to 85°C.

## RECOMMENDED OPERATING CONDITIONS

| Symbol            | Parameter                   |                  | Min | Max      | Unit |
|-------------------|-----------------------------|------------------|-----|----------|------|
| $V_{CC}$          | Supply Voltage              |                  | 2   | 6        | V    |
| $V_{IN}, V_{OUT}$ | DC Input or Output Voltage  |                  | 0   | $V_{CC}$ | V    |
| $T_A$             | Operating Temperature Range |                  | –55 | +125     | °C   |
| $t_r, t_f$        | Input Rise or Fall Times    | $V_{CC} = 2.0$ V | –   | 1000     | ns   |
|                   |                             | $V_{CC} = 4.5$ V | –   | 500      | ns   |
|                   |                             | $V_{CC} = 6.0$ V | –   | 400      | ns   |

Functional operation above the stresses listed in the Recommended Operating Ranges is not implied. Extended exposure to stresses beyond the Recommended Operating Ranges limits may affect device reliability.

# MM74HC04

## DC CHARACTERISTICS (Note 3)

| Symbol          | Parameter                         | V <sub>CC</sub><br>(V) | Conditions                                                                             | T <sub>A</sub> = 25°C |                   | T <sub>A</sub> = -40°C<br>to 85°C | T <sub>A</sub> = -55°C<br>to 125°C | Unit |
|-----------------|-----------------------------------|------------------------|----------------------------------------------------------------------------------------|-----------------------|-------------------|-----------------------------------|------------------------------------|------|
|                 |                                   |                        |                                                                                        | Typ                   | Guaranteed Limits |                                   |                                    |      |
| V <sub>IH</sub> | Minimum HIGH Level Input Voltage  | 2.0                    |                                                                                        | –                     | 1.5               | 1.5                               | 1.5                                | V    |
|                 |                                   | 4.5                    |                                                                                        | –                     | 3.15              | 3.15                              | 3.15                               |      |
|                 |                                   | 6.0                    |                                                                                        | –                     | 4.2               | 4.2                               | 4.2                                |      |
| V <sub>IL</sub> | Maximum LOW Level Input Voltage   | 2.0                    |                                                                                        | –                     | 0.5               | 0.5                               | 0.5                                | V    |
|                 |                                   | 4.5                    |                                                                                        | –                     | 1.35              | 1.35                              | 1.35                               |      |
|                 |                                   | 6.0                    |                                                                                        | –                     | 1.8               | 1.8                               | 1.8                                |      |
| V <sub>OH</sub> | Minimum HIGH Level Output Voltage | 2.0                    | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub> ,<br> I <sub>OUT</sub>   ≤ 20 μA  | 2.0                   | 1.9               | 1.9                               | 1.9                                | V    |
|                 |                                   | 4.5                    |                                                                                        | 4.5                   | 4.4               | 4.4                               | 4.4                                |      |
|                 |                                   | 6.0                    |                                                                                        | 6.0                   | 5.9               | 5.9                               | 5.9                                |      |
|                 |                                   | 4.5                    | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub> ,<br> I <sub>OUT</sub>   ≤ 4.0 mA | 4.2                   | 3.98              | 3.84                              | 3.7                                |      |
|                 |                                   | 6.0                    | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub> ,<br> I <sub>OUT</sub>   ≤ 5.2 mA | 5.7                   | 5.48              | 5.34                              | 5.2                                |      |
| V <sub>OL</sub> | Maximum LOW Level Output Voltage  | 2.0                    | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IH</sub> ,<br> I <sub>OUT</sub>   ≤ 20 μA  | 0                     | 0.1               | 0.1                               | 0.1                                | V    |
|                 |                                   | 4.5                    |                                                                                        | 0                     | 0.1               | 0.1                               | 0.1                                |      |
|                 |                                   | 6.0                    |                                                                                        | 0                     | 0.1               | 0.1                               | 0.1                                |      |
|                 |                                   | 4.5                    | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IH</sub> ,<br> I <sub>OUT</sub>   ≤ 4.0 mA | 0.2                   | 0.26              | 0.33                              | 0.4                                |      |
|                 |                                   | 6.0                    | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IH</sub> ,<br> I <sub>OUT</sub>   ≤ 5.2 mA | 0.2                   | 0.26              | 0.33                              | 0.4                                |      |
| I <sub>IN</sub> | Maximum Input Current             | 6.0                    | V <sub>IN</sub> = V <sub>CC</sub> or GND                                               | –                     | ±0.1              | ±1.0                              | ±1.0                               | μA   |
| I <sub>CC</sub> | Maximum Quiescent Supply Current  | 6.0                    | V <sub>IN</sub> = V <sub>CC</sub> or<br>GND, I <sub>OUT</sub> = 0 μA                   | –                     | 2.0               | 20                                | 40                                 | μA   |

3. For a power supply of 5 V ±10% the worst case output voltages (V<sub>OH</sub>, and V<sub>OL</sub>) occur for HC at 4.5 V. Thus the 4.5 V values should be used when designing with this supply. Worst case V<sub>IH</sub> and V<sub>IL</sub> occur at V<sub>CC</sub> = 5.5 V and 4.5 V respectively. (The V<sub>IH</sub> value at 5.5 V is 3.85 V.) The worst case leakage current (I<sub>IN</sub>, I<sub>CC</sub>, and I<sub>OZ</sub>) occur for CMOS at the higher voltage and so the 6.0 V values should be used.

## AC CHARACTERISTICS (V<sub>CC</sub> = 5 V, T<sub>A</sub> = 25°C, C<sub>L</sub> = 15 pF, t<sub>r</sub> = t<sub>f</sub> = 6 ns)

| Symbol                              | Parameter                 | Conditions | Typ | Guaranteed Limit | Unit |
|-------------------------------------|---------------------------|------------|-----|------------------|------|
| t <sub>PHL</sub> , t <sub>PLH</sub> | Maximum Propagation Delay |            | 8   | 15               | ns   |

## AC CHARACTERISTICS (V<sub>CC</sub> = 2.0 V to 6.0 V, C<sub>L</sub> = 50 pF, t<sub>r</sub> = t<sub>f</sub> = 6 ns (unless otherwise specified))

| Symbol                              | Parameter                              | V <sub>CC</sub><br>(V) | Conditions | T <sub>A</sub> = 25°C |                   | T <sub>A</sub> = −40°C<br>to 85°C | T <sub>A</sub> = −55°C<br>to 125°C | Unit |
|-------------------------------------|----------------------------------------|------------------------|------------|-----------------------|-------------------|-----------------------------------|------------------------------------|------|
|                                     |                                        |                        |            | Typ                   | Guaranteed Limits |                                   |                                    |      |
| t <sub>PHL</sub> , t <sub>PLH</sub> | Maximum Propagation Delay              | 2.0                    |            | 55                    | 95                | 120                               | 145                                | ns   |
|                                     |                                        | 4.5                    |            | 11                    | 19                | 24                                | 29                                 |      |
|                                     |                                        | 6.0                    |            | 9                     | 16                | 20                                | 24                                 |      |
| t <sub>TLH</sub> , t <sub>THL</sub> | Maximum Output Rise and Fall Time      | 2.0                    |            | 30                    | 75                | 95                                | 110                                | ns   |
|                                     |                                        | 4.5                    |            | 8                     | 15                | 19                                | 22                                 |      |
|                                     |                                        | 6.0                    |            | 7                     | 13                | 16                                | 19                                 |      |
| C <sub>PD</sub>                     | Power Dissipation Capacitance (Note 4) |                        | (per gate) | 20                    | –                 | –                                 | –                                  | pF   |
| C <sub>IN</sub>                     | Maximum Input Capacitance              |                        |            | 5                     | 10                | 10                                | 10                                 | pF   |

4. C<sub>PD</sub> determines the no load dynamic power consumption, P<sub>D</sub> = C<sub>PD</sub> V<sub>CC</sub><sup>2</sup> f + I<sub>CC</sub> V<sub>CC</sub>, and the no load dynamic current consumption, I<sub>S</sub> = C<sub>PD</sub> V<sub>CC</sub> f + I<sub>CC</sub>.

## MM74HC04

### ORDERING INFORMATION

| Part Number  | Package                                          | Shipping <sup>†</sup>    |
|--------------|--------------------------------------------------|--------------------------|
| MM74HC04M    | SOIC-14, Case 751A-03<br>(Pb-Free, Halide-Free)  | 55 Units / Tube          |
| MM74HC04MTC  | TSSOP-14, Case 948G-01<br>(Pb-Free, Halide Free) | 96 Units / Tube          |
| MM74HC04MX   | SOIC-14, Case 751EF<br>(Pb-Free, Halide-Free)    | 2500 Units / Tape & Reel |
| MM74HC04MTCX | TSSOP-14, Case 948G-01<br>(Pb-Free, Halide Free) | 2500 Units / Tape & Reel |

<sup>†</sup>For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

# MECHANICAL CASE OUTLINE PACKAGE DIMENSIONS



SCALE 1:1

SOIC-14 NB  
CASE 751A-03  
ISSUE L

DATE 03 FEB 2016



## NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. DIMENSION b DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE PROTRUSION SHALL BE 0.13 TOTAL IN EXCESS OF AT MAXIMUM MATERIAL CONDITION.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD PROTRUSIONS.
5. MAXIMUM MOLD PROTRUSION 0.15 PER SIDE.

| DIM | MILLIMETERS |      | INCHES    |       |
|-----|-------------|------|-----------|-------|
|     | MIN         | MAX  | MIN       | MAX   |
| A   | 1.35        | 1.75 | 0.054     | 0.068 |
| A1  | 0.10        | 0.25 | 0.004     | 0.010 |
| A3  | 0.19        | 0.25 | 0.008     | 0.010 |
| b   | 0.35        | 0.49 | 0.014     | 0.019 |
| D   | 8.55        | 8.75 | 0.337     | 0.344 |
| E   | 3.80        | 4.00 | 0.150     | 0.157 |
| e   | 1.27 BSC    |      | 0.050 BSC |       |
| H   | 5.80        | 6.20 | 0.228     | 0.244 |
| h   | 0.25        | 0.50 | 0.010     | 0.019 |
| L   | 0.40        | 1.25 | 0.016     | 0.049 |
| M   | 0°          | 7°   | 0°        | 7°    |

## SOLDERING FOOTPRINT\*



DIMENSIONS: MILLIMETERS

\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

## GENERIC MARKING DIAGRAM\*



XXXXXX = Specific Device Code  
A = Assembly Location  
WL = Wafer Lot  
Y = Year  
WW = Work Week  
G = Pb-Free Package

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

STYLES ON PAGE 2

|                  |             |                                                                                                                                                                                     |
|------------------|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DOCUMENT NUMBER: | 98ASB42565B | Electronic versions are uncontrolled except when accessed directly from the Document Repository.<br>Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| DESCRIPTION:     | SOIC-14 NB  | PAGE 1 OF 2                                                                                                                                                                         |

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

SOIC-14  
CASE 751A-03  
ISSUE L

DATE 03 FEB 2016

STYLE 1:  
PIN 1. COMMON CATHODE  
2. ANODE/CATHODE  
3. ANODE/CATHODE  
4. NO CONNECTION  
5. ANODE/CATHODE  
6. NO CONNECTION  
7. ANODE/CATHODE  
8. ANODE/CATHODE  
9. ANODE/CATHODE  
10. NO CONNECTION  
11. ANODE/CATHODE  
12. ANODE/CATHODE  
13. NO CONNECTION  
14. COMMON ANODE

STYLE 2:  
CANCELLED

STYLE 3:  
PIN 1. NO CONNECTION  
2. ANODE  
3. ANODE  
4. NO CONNECTION  
5. ANODE  
6. NO CONNECTION  
7. ANODE  
8. ANODE  
9. ANODE  
10. NO CONNECTION  
11. ANODE  
12. ANODE  
13. NO CONNECTION  
14. COMMON CATHODE

STYLE 4:  
PIN 1. NO CONNECTION  
2. CATHODE  
3. CATHODE  
4. NO CONNECTION  
5. CATHODE  
6. NO CONNECTION  
7. CATHODE  
8. CATHODE  
9. CATHODE  
10. NO CONNECTION  
11. CATHODE  
12. CATHODE  
13. NO CONNECTION  
14. COMMON ANODE

STYLE 5:  
PIN 1. COMMON CATHODE  
2. ANODE/CATHODE  
3. ANODE/CATHODE  
4. ANODE/CATHODE  
5. ANODE/CATHODE  
6. NO CONNECTION  
7. COMMON ANODE  
8. COMMON CATHODE  
9. ANODE/CATHODE  
10. ANODE/CATHODE  
11. ANODE/CATHODE  
12. ANODE/CATHODE  
13. NO CONNECTION  
14. COMMON ANODE

STYLE 6:  
PIN 1. CATHODE  
2. CATHODE  
3. CATHODE  
4. CATHODE  
5. CATHODE  
6. CATHODE  
7. CATHODE  
8. ANODE  
9. ANODE  
10. ANODE  
11. ANODE  
12. ANODE  
13. ANODE  
14. ANODE

STYLE 7:  
PIN 1. ANODE/CATHODE  
2. COMMON ANODE  
3. COMMON CATHODE  
4. ANODE/CATHODE  
5. ANODE/CATHODE  
6. ANODE/CATHODE  
7. ANODE/CATHODE  
8. ANODE/CATHODE  
9. ANODE/CATHODE  
10. ANODE/CATHODE  
11. COMMON CATHODE  
12. COMMON ANODE  
13. ANODE/CATHODE  
14. ANODE/CATHODE


STYLE 8:  
PIN 1. COMMON CATHODE  
2. ANODE/CATHODE  
3. ANODE/CATHODE  
4. NO CONNECTION  
5. ANODE/CATHODE  
6. ANODE/CATHODE  
7. COMMON ANODE  
8. COMMON ANODE  
9. ANODE/CATHODE  
10. ANODE/CATHODE  
11. NO CONNECTION  
12. ANODE/CATHODE  
13. ANODE/CATHODE  
14. COMMON CATHODE

|                  |             |                                                                                                                                                                                     |
|------------------|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DOCUMENT NUMBER: | 98ASB42565B | Electronic versions are uncontrolled except when accessed directly from the Document Repository.<br>Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| DESCRIPTION:     | SOIC-14 NB  | PAGE 2 OF 2                                                                                                                                                                         |

**onsemi** and **onsemi** are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.


**SOIC14**  
CASE 751EF  
ISSUE O

DATE 30 SEP 2016



**NOTES:**

- A. CONFORMS TO JEDEC MS-012, VARIATION AB, ISSUE C
- B. ALL DIMENSIONS ARE IN MILLIMETERS
- C. DIMENSIONS DO NOT INCLUDE MOLD FLASH OR BURRS
- D. LAND PATTERN STANDARD: SOIC127P600X145-14M
- E. CONFORMS TO ASME Y14.5M, 2009



|                         |                    |                                                                                                                                                                                  |
|-------------------------|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>DOCUMENT NUMBER:</b> | <b>98AON13739G</b> | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>SOIC14</b>      | <b>PAGE 1 OF 1</b>                                                                                                                                                               |

ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

### TECHNICAL PUBLICATIONS:

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

### ONLINE SUPPORT: [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at  
[www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)